

Retarder proofer with tilting doors - BFP

Cooling unit ready for use with refrigerating fluid R 404 A preserving the ozone layer
 Control panel with electronic controls (BFA and BFC alike) with reheating by levels and/or constant increase of the temperature (degree per degree), with stabilisation of the temperature in hot cycle, and possibility of "dormillon" (if after a period of 45 min following programmed fermentation cycle, nobody has withdrawn the product, the cabinet goes back to a temperature of 15° C : values are adjustable)
 Adjustable humidity (between 30 and 99%)
 Easy cleaning

Construction

- Enclosures: 60 mm isothermal hot electro-plated zinc panels, pre-lacquered, painted and coated with a protective polyethylene covering
- BFP is fitted with 5 tilting doors :
- 18 levels with a spacing of 80 mm
- 22 levels with a spacing of 65 mm
- Injected with polyurethane foam 40 kg/m³
- Easily adjustable slides for holding the baking trays (trays not supplied)
- Smooth interior finish with rounded corners
- 48 adjustable slides for holding the baking trays (Trays and linen canvas not supplied)
- 3 wheels and 2 adjustable foot
- The cabinets are fitted with mixed hook racks for different adaptations
- Power supply : 230 V (PH + N + T) single phase 50 Hz

